

# Centra

The economic solution for **HEAVY COMMERCIAL** applications



## PRODUCT INFORMATION

Level of use	EN 653	23 - 34 - 43
Total thickness	EN 428	2,00 mm
Wear layer	EN 429	0,70 mm
Wear layer PUR treatment		Hyperguard+
Total weight/m	EN 430	ca. 2.543 g/m <sup>2</sup>
Heterogeneous PVC		

## SIZE & PACKING

Width	EN 426	2 - 4 m
Standard Length	EN 426	ca. 25 m
Weight of standard roll		ca. 131kg - 262kg

## TEST RESULTS

Inflammability	EN 13501	Bfl-S1
Slip resistance	EN 13893	DS
Slip restraint	DIN 51130	R10
Residual indentation	EN 433	0,05 mm
Furniture leg resistance	EN 424	Very good
Curling	EN 434	≤ 8 mm
Electrical resistance	EN 1081	10 <sup>9</sup> Ohm
Static electrical propensity	EN 1815	<2kV
Dimensional stability	EN 434	0,05%
Heat insulation	EN 12524	0,25 w/(m.K)
Abrasion group	EN 660-2	Groupe T
Formaldehyde group	EN 717-1	E1
Acoustic insulation	ISO 717-1	ΔLw 7 dB
Castor chair resistance	EN 425	Very good
Light fastness	ISO 105B02	6
Underfloor heating	EN 12524	Suitable
Resistance to chemicals	EN 423	Very good
Hot welding		Welding rods on demand
Warranty (year)		5



EN 14041 : 2004  
06